

PRODUCT NAME: YELLOW EPOXY

HMIS CODES: H F R P

PRODUCT CODE: 18-6-A

1 0 0 J

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Pruett-Schaffer Chemical Co.
ADDRESS: 3327 Stafford Street Pittsburgh PA 15204
EMERGENCY PHONE: 1-800-633-8253 INFORMATION PHONE: 1-412-771-2000
REVISION DATE: 10/14/08 NAME OF PREPARER: Robert P. Barry

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 6 columns: REPORTABLE COMPONENTS, CAS NUMBER, VAPOR PRESSURE (mm Hg @ TEMP Deg F), WEIGHT PERCENT. Rows include Modified Bisphenol F Epoxy and Yellow Iron Oxide, inert pigment.

No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.

LEGEND: (C)=Ceiling limit; (S)=Skinlimit; (STEL)=Short Term Exposure Limit; (Mppcf)=Million Particles Per Cubic Foot; (TWA)=8 HR Time Weighted Average.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: n/a SPECIFIC GRAVITY: 1.19
VAPOR DENSITY: Heavier than air. EVAPORATION RATE: Slower than ether.
COATING VOC: 0.00 lb/gl MATERIAL VOC: 0.00 lb/gl
ORGANIC SOLVENT, PERCENT BY WEIGHT: 0.000
ORGANIC SOLVENT, PERCENT BY VOLUME: 0.000
COATING DENSITY, LB/GAL: 9.915
SOLUBILITY IN WATER: Insoluble.
APPEARANCE AND ODOR: Viscous, opaque liquid with a slight odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Greater than 141 deg F. METHOD USED: PMCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a UPPER: n/a
EXTINGUISHING MEDIA: Foam, alcohol foam, CO2, dry chemical, water fog.
SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus and full protective clothing.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Pressure may build up in tightly closed

containers exposed to fire which may result in rupture. Keep containers cooled with water spray.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable

CONDITIONS TO AVOID: Excessive heat, freezing temperatures, corrosive atmospheres or liquids which may damage containers.

INCOMPATIBILITY (MATERIALS TO AVOID): May react vigorously with strong acids, bases, and oxidizers.

MATERIAL SAFETY DATA SHEET

Page: 2

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: May include carbon dioxide, carbon monoxide, hydrogen chloride, and other toxic gases.

HAZARDOUS POLYMERIZATION: Will not occur.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Effects vary among individuals and may include nausea and irritation of the nose, throat, and upper respiratory tract. Effects vary among individuals, and effects may be increased by heating this material.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Eye contact may cause irritation, redness, and tearing. Skin contact may result in irritation, redness, dermatitis, or allergic reaction. May cause sensitization in individuals allergic to the poison ivy family of plants. This material is non-toxic dermally, with LD50 > 2g/kg.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: The oral toxicity of this material has not been determined, ingestion of large amounts may cause gastrointestinal irritation, vomiting, nausea, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC): Breathing high concentrations of aerosols or mists of this material may cause temporary irritation of the eyes, nose, throat, respiratory tract, and skin. May produce allergic reactions in individuals allergic to the poison ivy family of plants (Rhus family). This product is a mild sensitizer, repeated or prolonged overexposure to the skin may result in irritation or dermatitis. NOTE: This product contains trace amounts of formaldehyde and epichlorohydrin (CAS 106-89-8, ACGIH TLV=2ppm skin, OSHA PEL=5ppm) which have caused cancer in laboratory animals, but are not confirmed human carcinogens.

CARCINOGENICITY: NTP: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Allergic skin conditions, eczema, dermatitis. Respiratory symptoms associated with preexisting lung disorders may be aggravated by exposure to this material.

EMERGENCY AND FIRST AID PROCEDURES: INHALATION OVEREXPOSURE: Remove person to fresh air, If breathing stops, apply artificial respiration and seek immediate medical attention. NOTE: Use supplied-air respirator for rescue in enclosed areas. EYE CONTACT: Flush with large amounts of tepid water for at least 15 minutes, get medical attention. INGESTION: Do not induce vomiting, if aspirated material can cause chemical pneumonitis or pulmonary edema. Drink 2 glasses of milk or water to dilute and contact physician or poison center. SKIN: Wash with soap and water, avoid repeated contact.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====
MATERIAL SAFETY DATA SHEET

Page: 3

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entry into sewers or surface waters. Recover free liquid by shoveling into container, or add absorbent such as sand or earth to spill and sweep up. Provide ventilation, wear a respirator. Notify proper authorities if spill contaminates land or waterways.

WASTE DISPOSAL METHOD: Dispose of in chemical landfill or incinerate assuring conformity to all applicable local, state, and federal governing regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not expose to direct sun or freezing temperatures, store inside away from extreme temperature variations. Protect containers from physical damage. Keep containers tightly closed when not in use. Do not inhale aerosols or mists, use with adequate ventilation and wear a respirator. Do not store with food or animal feed.

OTHER PRECAUTIONS: Do not cut, weld, grind, drill, solder, or braze on or near containers whether full or empty. Do not reuse containers without professional reconditioning and testing. Do not remove warning labels from containers.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION: Spraying this product in poorly ventilated areas may require the use of a respirator. Use Mine Safety Appliance respirator #448849 with mist filter (or equivalent) if air monitoring demonstrates that the concentration of listed hazardous materials carried by aerosols exceeds recommended TLV's.

VENTILATION: Use good general mechanical ventilation and local exhaust adequate to reduce the concentration of aerosols or mists carrying listed hazardous materials to below the Threshold Limit Value(s).

PROTECTIVE GLOVES: Use of gloves is recommended, use chemically resistant type.

EYE PROTECTION: Use is recommended, use splash goggles or full face shields as necessary.

OTHER PROTECTIVE CLOTHING: Use impervious apron or coveralls to prevent contaminating street clothes which may result in prolonged exposure. The use of head caps or helmets is recommended.

WORK AND HYGIENIC PRACTICES: Eye washes and safety showers in the workplace are recommended. Practice good industrial hygiene when using this product: After using this product, do not smoke or eat until washing thoroughly. Remove saturated clothing or shoes at once and launder before reuse.

===== SECTION IX - MISCELLANEOUS =====

ADDITIONAL HAZARDOUS MATERIAL INFORMATION:

SHIPPING INFORMATION:

DISCLAIMER:

The information and recommendations contained herein were believed to be accurate at the time of preparation or obtained from sources believed to be generally reliable. Direct testing of this product under all conceivable conditions of use has not been done. Information given herein is given in good faith, however Pruett-Schaffer Chemical Corporation makes no warranty concerning its accuracy and will not be held liable for claims relating to any party's use of or reliance on this information.