

PRODUCT NAME: Inorganic Zinc Paint (Single Package)

HMIS CODES: H F R P
2 2 1 X

PRODUCT CODE: 99-12886

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Pruett-Schaffer Chemical Co.
 ADDRESS: 3327 Stafford Street Pittsburgh PA 15204
 EMERGENCY PHONE: 1-800-633-8253 INFORMATION PHONE: 1-412-771-2000
 REVISION DATE: 03/29/07 NAME OF PREPARER: Robert P. Barry

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP Deg F	WEIGHT PERCENT
* Zinc metal ACGIH TLV: 5 mg/m3. OSHA PEL: 5 mg/m3 TWA, 10 mg/m3 STEL	7440-66-6	0 0	62.30
Petroleum Solvent ACGIH TLV: 5mg/m3, OSHA PEL: 5mg/m3, Other TLV: (mist)	64742-94-5	.15 77	8.12
Mica, inert filler ACGIH TLV: 3 mg/m3, OSHA PEL: 20 Mppcf	12001-26-2	0 0	5.16
* Trimethylbenzene ACGIH TLV: 25 ppm TWA. OSHA PEL: 25 ppm TWA.	95-63-6	0 0	4.51
Ethyl Alcohol (ethanol) ACGIH TWA8 TLV: 1000ppm or 1880 mg/m3. OSHA PEL: TWA8 1000ppm.	64-17-5	50 68	2.73
Amorphous fused silica OSHA PEL & ACGIH: 20 mppcf	68909-20-6	0 0	1.96
* Ethylene Glycol Monopropyl Ether, 2-propoxyethanol Manufacturer recommendation: 20 ppm TWA8 (S), 60ppm STEL (S).	12807-30-91.368	1.51	
Zinc Oxide ACGIH TLV: 10 mg/m3. OSHA PEL: 10 mg/m3 TWA total dust, 5 mg/m3 respirable	1314-13-2	0 0	1.28
* Calcium Oxide ACGIH TLV: 2 mg/m3. OSHA PEL: mg/m3 TWA total dust	1305-78-8	0 0	0.32
* Cumene ACGIH TLV: 50 ppm (S). OSHA PEL: 50 ppm (S).	98-82-8	0 0	0.19
* Ethyl Benzene OSHA: 100ppm TWA, 125ppm TWA STEL	100-41-4	0 0	0.06
* Lead ACGIH TLV: 0.15 mg/m3. OSHA PEL: mg/m3 TWA total dust	7439-92-1	0 0	0.00
* Cadmium ACGIH TLV: 0.01 mg/m3. OSHA PEL: mg/m3 TWA total dust	7440-43-9	0 0	0.00

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

LEGEND: (C)=Ceiling limit; (S)=Skinlimit; (STEL)=Short Term Exposure Limit;
 (Mppcf)=Million Particles Per Cubic Foot; (TWA)=8 HR Time Weighted Average.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 174 deg F - 301 deg F SPECIFIC GRAVITY: 2.34
 VAPOR DENSITY: Heavier than air. EVAPORATION RATE: Slower than ether.
 COATING VOC: 3.34 lb/gl MATERIAL VOC: 3.34 lb/gl
 ORGANIC SOLVENT, PERCENT BY WEIGHT: 17.137
 ORGANIC SOLVENT, PERCENT BY VOLUME: 46.797
 COATING DENSITY, LB/GAL: 19.482
 SOLUBILITY IN WATER: Insoluble.
 APPEARANCE AND ODOR: Viscous, opaque liquid with a paint thinner-like odor.

CHRONIC EFFECTS OF ETHYLBENZENE OVEREXPOSURE

The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene (a component of xylol) and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans.

CHRONIC EFFECTS OF LEAD OVEREXPOSURE

The International Agency for Research on Cancer (IARC) lists lead as a possible human carcinogen (Group 2B), based on sufficient evidence for carcinogenicity in experimental animals. However, there is inadequate evidence of the carcinogenicity of lead in humans.

CHRONIC EFFECTS OF CADMIUM OVEREXPOSURE

The International Agency for Research on Cancer (IARC) lists cadmium as a possible human carcinogen (Group 2B), based on sufficient evidence for carcinogenicity in experimental animals. However, there is inadequate evidence of the carcinogenicity of cadmium in humans.

CHRONIC EFFECTS OF ZINC OVEREXPOSURE

Inhalation of high levels of zinc may result in tightness of chest, metallic taste, cough, dizziness, fever, chills, headache, nausea, and dry throat. Overexposure may produce symptoms known as metal fume fever or "zinc shakes"; an acute, self-limiting condition without recognized complications. Symptoms of zinc shakes include: chills, fever, muscular pain, nausea and vomiting. Symptoms resulting from overexposure to zinc usually disappear within 24 hours. Symptomatic treatment, such as bed rest and possibly aspirin is recommended to provide relief from fever and chills.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Overexposure to solvent fumes may aggravate anesthesia, respiratory tract disease or pre-existing lung disorders, nausea, and vomiting.

EMERGENCY AND FIRST AID PROCEDURES: INHALATION OVEREXPOSURE: Remove person to fresh air, If breathing stops, apply artificial respiration and seek immediate medical attention. NOTE: Use supplied-air respirator for rescue in enclosed areas. EYE CONTACT: Flush with large amounts of tepid water for at least 15 minutes, get medical attention. INGESTION: Do not induce vomiting, if aspirated material can cause chemical pneumonitis or pulmonary edema. Drink 2 glasses of milk or water to dilute and contact physician or poison center. SKIN: Wash with soap and water, avoid repeated contact.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Dike to prevent entry into sewers or surface waters. Recover free liquid by shoveling into container using non-sparking tools, or add absorbent such as sand or earth to spill and sweep up. Provide ventilation, wear a respirator. Notify proper authorities if spill contaminates land or waterways.

WASTE DISPOSAL METHOD: Store soaked rags or absorbent material in airtight containers to prevent spontaneous combustion of material. Absorbent materials may emit flammable vapors. Dispose of in chemical landfill or incinerate assuring conformity to all applicable local, state, and federal governing regulations. Store soaked rags or absorbent material in airtight containers to prevent spontaneous combustion of material. Dispose of in chemical landfill or incinerate assuring conformity to all applicable local, state, and federal governing regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not expose to flame, sparks, or other sources of ignition. Use non-sparking alloy tools and explosion-proof

equipment for handling. The need for grounding and bonding of containers in accordance with OSHA 29 CFR 1910.106 and NFPA 77 should be assessed before transferring product. Store inside away from extreme temperature variations. Protect containers from physical damage. Keep containers tightly closed when not in use. Do not inhale vapors or mists, use with adequate ventilation and wear a respirator. Do not store with food or animal feed.

OTHER PRECAUTIONS: Do not cut, weld, grind, drill, solder, or braze on or near containers whether full or empty. Do not reuse containers without professional reconditioning and testing. Do not remove warning labels from containers.

=====
SECTION VIII - CONTROL MEASURES
=====

RESPIRATORY PROTECTION: Using this product in poorly ventilated areas may require the use of a respirator. Use Mine Safety Appliance respirator #448849 with organic vapor cartridge and mist filter (or equivalent) if air monitoring demonstrates that the concentration of listed hazardous materials exceeds the recommended TLV's. In enclosed areas where ventilation is not used, wear a Mine Safety Appliance #475217 pressure/demand air-supplied respirator or equivalent.

VENTILATION: Use good general mechanical ventilation and local exhaust adequate to reduce the concentration of vapors or mists of the listed hazardous materials to below the Threshold Limit Value(s) and the Lower Explosion Limit. Ventilation equipment must be explosion proof. Use good general mechanical ventilation and local exhaust adequate to reduce the concentration of vapors or mists of the listed hazardous materials to below the Threshold Limit Value(s) and the Lower Explosion Limit.

PROTECTIVE GLOVES: Use of gloves is recommended, use chemically resistant type.

EYE PROTECTION: Use is recommended, use splash goggles or full face shields as necessary.

OTHER PROTECTIVE CLOTHING: Use impervious apron or coveralls to prevent contaminating street clothes which may result in prolonged exposure. The use of head caps or helmets is recommended.

WORK AND HYGIENIC PRACTICES: Eye washes and safety showers in the workplace are recommended. Practice good industrial hygiene when using this product: After using this product, do not smoke or eat until washing thoroughly. Remove saturated clothing or shoes at once and launder before reuse.

=====
SECTION IX - MISCELLANEOUS
=====

ADDITIONAL HAZARDOUS MATERIAL INFORMATION:

SHIPPING INFORMATION:

UN/NA ID No.: NA 1993
DOT HAZARD CLASS: NONE
PACKING GROUP: III
DOT HAZARDOUS MATERIAL PROPER SHIPPING NAME: Combustible Liquid, Paint

DISCLAIMER:

The information and recommendations contained herein were believed to be accurate at the time of preparation or obtained from sources believed to be generally reliable. Direct testing of this product under all conceivable conditions of use has not been done. Information given herein is given in good faith, however Pruett-Schaffer Chemical Corporation makes no warranty concerning its accuracy and will not be held liable for claims relating to any party's use of or reliance on this information.

